

SIMATIC DP, HART ANALOG INPUT SM 331, 2 AI, 0/4 - 20mA
HART, UP TO HART REV. 5.0, FOR ET200M WITH IM153-2, 1 X 20
PIN



Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	180 mA
from backplane bus 5 V DC, max.	100 mA
Output voltage	
Power supply to the transmitters	
• present	Yes
• Rated value (DC)	15 V; at 22 mA
• short-circuit proof	Yes; approx. 30 mA
• No-load voltage (DC)	29.6 V
Power loss	
Power loss, typ.	4.5 W
Analog inputs	
Number of analog inputs	2

permissible input current for current input (destruction limit), max.	40 mA
Input ranges	
• Current	Yes
Input ranges (rated values), currents	
• 0 to 20 mA	Yes
• Input resistance (0 to 20 mA)	50 Ω
• 4 mA to 20 mA	Yes
• Input resistance (4 mA to 20 mA)	50 Ω
Cable length	
• shielded, max.	400 m
Analog value generation for the inputs	
Measurement principle	Sigma Delta
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit; 10 bit to 15 bit + sign
• Integration time, parameterizable	Yes
• Integration time (ms)	2,5 / 16,67 / 20 / 100 ms
• Basic conversion time, including integration time (ms)	2.5 / 16.67 / 20 / 100 (1 channel enabled); 7.5 / 50 / 60 / 300 (2 channels enabled)
• Interference voltage suppression for interference frequency f1 in Hz	10 / 50 / 60 / 400 Hz
Encoder	
Connection of signal encoders	
• for current measurement as 2-wire transducer	Yes
• for current measurement as 4-wire transducer	Yes
Errors/accuracies	
Linearity error (relative to input range), (+/-)	0.01 %
Temperature error (relative to input range), (+/-)	0.01 %/K
Crosstalk between the inputs, min.	130 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.05 %
Operational error limit in overall temperature range	
• Current, relative to input range, (+/-)	0.45 %; From 0/4 to 20 mA
Basic error limit (operational limit at 25 °C)	
• Current, relative to input range, (+/-)	0.1 %; From 0/4 to 20 mA
Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$, f_1 = interference frequency	
• Series mode interference (peak value of interference < rated value of input range), min.	60 dB
• Common mode interference, min.	130 dB
Interrupts/diagnostics/status information	
Diagnostic functions	Yes; can be set in parameters, red LED, alarm message

Alarms	
• Diagnostic alarm	Yes; Parameterizable
• Limit value alarm	Yes; Parameterizable, channels 0 and 1
Diagnostic messages	
• Diagnostic information readable	Yes
• Overrange	Yes; Red LED, signal
• Wire-break in signal transmitter cable	Yes; Red LED, signal
• Short-circuit of the signal encoder cable	Yes; Red LED, signal
• HART communication active	Yes; green LED (H)
Diagnostics indication LED	
• Group error SF (red)	Yes
• Channel fault indicator F (red)	Yes
Ex(i) characteristics	
Module for Ex(i) protection	Yes
Maximum values of input circuits (per channel)	
• Co (permissible external capacity), max.	62 nF
• Io (short-circuit current), max.	96.1 mA
• Lo (permissible external inductivity), max.	3 mH
• Po (power of load), max.	511 mW
• Uo (output no-load voltage), max.	26 V
• Um (fault voltage), max.	250 V; DC
• Ta (permissible ambient temperature), max.	0.6 °C
Potential separation	
Potential separation analog inputs	
• between the channels	Yes
• between the channels and backplane bus	Yes
Permissible potential difference	
between the inputs (UCM)	60 V DC/30 V AC
Isolation	
tested with	
• Channels against backplane bus and load voltage L+	1500 V AC
• Channels among one another	1500 V AC
• Load voltage L+ against backplane bus	500 V DC
Standards, approvals, certificates	
FM approval	Available soon
Use in hazardous areas	
• Type of protection acc. to EN 50020 (CENELEC)	[Ex ib] IIC

- Type of protection acc. to FM
- Type of protection acc. to KEMA
- Test number KEMA

Class I, Division 2, Group A, B, C, D T4; Class I, Zone 2, Group IIC T4
 II3 (2) G Eex nA [ib] IIC T4
 KEMA 97 ATEX 3039X

Ambient conditions

Ambient temperature during operation

- max. 60 °C

Dimensions

Width	40 mm
Height	125 mm
Depth	120 mm

Weights

Weight, approx.	260 g
-----------------	-------

last modified: 08/29/2017