
Product data sheet Characteristics

TSXRKY12EX

extendable rack - for multi-racks configuration - 12 slots - IP20



Commercial status

Discontinued: 31 December 2018

(!) Restricted Sales for Services

Main

Range of product

Product or component type

Product specific application	For multi-racks configuration	
Complementary		<u> </u>
Number of slots	12	1
Product compatibility	TSXP57 processor I/O module Specific application module TSXPSY power supply	4
Electrical connection	2 connectors female SUB-D 9 (remote connection of bus X)	
Fixing mode	By 4 M6 screws (panel) By clips (35 mm symmetrical DIN rail)	
Marking	CE	

Modicon Premium Automation platform

Extendable rack

2.34 kg

Environment

Net weight

Standards	CSA C22.2 No 213 Class I Division 2 Group A		
	CSA C22.2 No 213 Class I Division 2 Group D		
	92/31/EEC	0 0 0 0	
	CSA C22.2 No 213 Class I Division 2 Group B		
	93/68/EEC	and	
	89/336/EEC	ţ	
	CSA C22.2 No 142	substitute for and is	
	UL 508	: <u>=</u>	
	CSA C22.2 No 213 Class I Division 2 Group C		
	73/23/EEC		
	IEC 61131-2	4	
Product certifications	ABS	documentation is not intended as	
	GL	. <u>=</u>	
	DNV	. <u>v</u>	
	LR	j.	
	BV	t et	
	RINA	Ē	
	RMRS	200	
Ambient air temperature for operation	060 °C	- Sid	
Ambient air temperature for storage	-2570 °C	-i-	
Relative humidity	1095 % without condensation for operation	Disclaimer	

5...95 % without condensation for storage

Operating altitude	02000 m
Protective treatment	TC
IP degree of protection	IP20
Pollution degree	2

Contractual warranty

Warranty	18 month	

TSXRKY12EX is replaced by:

Standard environment BMEXBP1200

rack X80 - 12 slots - Ethernet backplane

Qty 1

Reason for Substitution: End of life | Substitution date: 31 December 2018

